



Intertek
C22.2 no113
UL 1812



LIGHT COMMERCIAL SERIES

HRV

H1800A-Fi-N

Heat Recovery Ventilator
1580 CFM at 0.4 in.w.g (ESP)

Made in Canada	15 YEAR WARRANTY	2 YEAR WARRANTY
	CORE	OTHER PARTS

PRODUCT DESCRIPTION

The H1800A-Fi-N (aluminum core) heat recovery ventilators provide up to 1580 cubic feet per minute of fresh outdoor air while exhausting an equivalent amount of stale indoor air, creating a well-balanced ventilation system.

These ventilators are recommended for midsized non-residential spaces or dedicated zones within larger buildings such as classrooms, common areas of residential complexes, pools and indoor parking garages.

Designed for versatile indoor installation, Aldes light commercial ventilators can fit almost anywhere and still provide easy access to the internal components for quick maintenance. The units also offer a choice of five continuous operation speeds and a demand-controlled high speed exchange mode.

KEY FEATURES

Electronically and independently adjustable supply and exhaust blowers (FlexControl).

Painted, heavy-gauge galvanized steel cabinets are attractive, rust-resistant and extremely durable.

Doors on both sides of the unit to allow easy access to filters, cores and motors, no matter the installation constraints.

Fan exhaust frost protection, or optional recirculation defrost kit (factory installed or upgraded in the field).

Four efficient, totally enclosed motors with backward inclined impellers.



Plate Exchanger

Material: Aluminum

Casing

Material: Painted galvanized steel 22GA
Insulation: 1" (25 mm) Fiberglass with FSK
Drain Connection: Ø 1/2" (Ø 13 mm)
Duct Connections: 24" x 8" (610mm x 203mm)
Width: 45-5/8 (1158mm)
Height: 29-5/8 (753mm)
Depth: 48-7/8 (1242mm)
Unit Weight: 245 lb (111 kg); 258 lb (117 kg) with recirculation



Mounting

Supplied with base rails. Support rods not included.



Electrical Requirements

120V/1p/60 Hz: FLA 13.8A, MCA 14.7A, MOP 20A
Terminal block for direct wiring to the building's electrical system.
Fused disconnect not included.



Frost Control

Cycles controlled by a temperature sensor when outdoor temperatures fall below 23°F (-5°C).

- Standard: Exhaust Defrost
- Optional: Recirculation Defrost (P/N 683960)



Blowers

Four backward-inclined motorized impeller, direct-drive PSC, variable speed, external rotor




Filters

Additional Air Pressure Drop with Optional Filters			Filter type	P/N	#Filters in pack
Filter Type	Airflow CFM (L/S)		Aluminum	612414	3
	1000 (472)	1400 (661)	MERV 8	612411	3
MERV 8	0.08	0.15	High Efficiency	612412	3
High Efficiency	0.35	0.48			

Note: This model requires a total of 6 filters. Make sure to get enough packs to meet the required amount.

DIMENSIONS



CONTROLS


0-10 VDC inputs (for supply and exhaust) or multiple fixed speed options

Low-voltage dry contact (24 VAC, 20 VA) for:

- Occupancy Control (On/Off)
- Interlock contacts
- Optional Recirculation Mode

24 VAC, 10 VA output for supply and exhaust dampers (by others)

Compatible with :



Digital Multifunction Control (P/N 611242-FC)



LCD Electronic Multifunction Control (P/N 611227)



20/40/60 Minute Timer (P/N 611228)





Speed Control (Low/Intermittent/High) (P/N 611229)



Mode Control (exchange or recirculation) (P/N 611230)

BACnet™ interface (P/N 611235)

PERFORMANCE



Project:		Architect:	
Location:		Engineer:	
Model #:		Contractor:	
Quantity:		Comments:	
Submitted By:			
Date:			

For more information, contact your Aldes sales advisor, visit aldes-na.com, call 1.800.255.7749, or find us on

